

Introducing the Industry's First Fire Extinguisher Designed to be Maintained and Recharged by the Owner.

Owner Maintained reduces costs by eliminating the 6-year internal exam and third-party service requirements.*

Universal Design is easy for a left or right-handed person to operate, saving time when seconds count.

CO₂ Cartridge-Based design is more reliable and safer than stored pressure extinguishers.

Engineered Polymer construction is corrosion-proof, resists impacts, and is 100% recyclable for sustainability.

High Efficiency valve and nozzle assembly improve agent discharge, knocking down flames faster and giving the user more protection.

Recharge Kit (sold separately) has everything you need to recharge your Rusoh® Eliminator® fire extinguisher in minutes and put it back into service.



*Some states may require additional maintenance/licensing. Contact your sales representative and/or local fire official for more information.

RUSOH INC. EXTINGUISHER SPECIFICATIONS

Agent Type	2.5 lb ABC Dry Chemical	5 lb ABC* Dry Chemical	10 lb ABC* Dry Chemical	10 lb ABC* High-Flow Dry Chemical
Stock:	09306	09300	09308	09314
UL & ULC Rating:	1A:10B:C	3A:40B:C	4A:80B:C	1A:20B:C
Capacity:	2.5 lb (1.1 kg) nom	5 lb (2.3 kg) nom	10 lb (4.5 kg) nom	10 lb (4.5 kg) nom
Agent:	MAP**	MAP**	MAP**	MAP**
Weight:	5.95 lbs (2.7 kg)	12.1 lbs (5.5 kg)	19.5 lb (8.8 kg)	19.5 lb (8.8 kg)
Height:	14.68 in (37.29 cm)	16.75 in (42.54 cm)	21.5 in (54.6 cm)	21.5 in (54.6 cm)
Width:	7.13 in (18.11 cm)	8.5 in (21.59 cm)	10.4 in (26.4 cm)	10.4 in (26.4 cm)
Depth:	5.05 in (12.83 cm)	5.7 in (14.47 cm)	6.2 in (15.8 cm)	6.2 in (15.8 cm)
Discharge Range:	6-8 ft (1.8-2.4 m)	12-18 ft (4-6 m)	15-21 ft (4.6-6.4 m)	15-25 ft (4.6-7.6 m)
Discharge Time:	> 8 secs	>13 secs	>21 secs	>9 secs
ANSI/UL 299 & 711:	Yes	Yes	Yes	Yes
USCG Approval†:	Type BC - Size	Type A-Size Type BC-Size	Type A-Size Type BC-Size	Type A-Size Type BC-Size
Warranty:	6 years	8 Years	8 Years	8 Years